


BENCH DRILLING CATALOGUE

 **qonar**






GONAR Co. Ltd. has been operating on the international market since 1974. We have over 40 years of experience in manufacturing of mining, tunnelling & geotech tools. Using raw materials only from certified suppliers in combination with high-tech innovative production facilities, we can guarantee high quality of fully carburised drill steels. Our R&D Department equipped with a testing lab and our Sinter Plant producing carbides in controlled vacuum ovens, assure high manufacturing quality.


We offer a wide range of products with carbide sinters and have the possibility to quickly turn around on prototype tooling and urgent requirements. To sum up we are a dynamic company with an aim to become leaders in technology and product innovation.






Bits, Rods, Couplings, Bit Adapters

– T38	str. 2-11
– T45	str. 12-21
– T51	str. 22-31
– ST58	str. 32-33
– GT60	str. 34-40



Button bit – DROP CENTER




Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
64	2 ½	-	4x8	8x10	5x9	1,8	B50064T3805R
64	2 ½	-	4x8	8x10	5x9	1,8	B50064T3805S
70	2 ¾	-	4x8	8x11	5x10	2,2	B50070T3805R
70	2 ¾	-	4x8	8x11	5x10	2,2	B50070T3805S
76	3	-	4x8	8x12	5x11	2,5	B50076T3805R
76	3	-	4x8	8x12	5x11	2,5	B50076T3805S
89	3 ½	-	4x9	8x13	5x12	3,4	B50089T3805R
89	3 ½	-	4x9	8x13	5x12	3,4	B50089T3805S
102	4	-	4x9	8x13	6x13	4,7	B50102T3805R
102	4	-	4x9	8x13	6x13	4,7	B50102T3805S

R – spherical

S – semi-ballistic

Button bit – DROP CENTER – RETRAC



Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
64	2 ½	-	4x8	8x10	5x9	2,2	B51064T3805R
64	2 ½	-	4x8	8x10	5x9	2,2	B51064T3805S
70	2 ¾	-	4x8	8x11	5x10	2,8	B51070T3805R
70	2 ¾	-	4x8	8x11	5x10	2,8	B51070T3805S
76	3	-	4x8	8x12	5x11	3,6	B51076T3805R
76	3	-	4x8	8x12	5x11	3,6	B51076T3805S
89	3 ½	-	4x9	8x13	5x12	5,5	B51089T3805R
89	3 ½	-	4x9	8x13	5x12	5,5	B51089T3805S
102	4	-	4x9	8x13	6x13	7,3	B51102T3805R
102	4	-	4x9	8x13	6x13	7,3	B51102T3805S

R – spherical

S – semi-ballistic

Button bit – DROP CENTER




Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
64	2 ½	-	3x8	9x10	4x9	1,8	B60064T3805R
64	2 ½	-	3x8	9x10	4x9	1,8	B60064T3805S
70	2 ¾	-	3x8	9x11	4x10	2,1	B60070T3805R
70	2 ¾	-	3x8	9x11	4x10	2,1	B60070T3805S
76	3	-	3x9	9x12	4x10	2,4	B60076T3805R
76	3	-	3x9	9x12	4x10	2,4	B60076T3805S
89	3 ½	-	3x10	9x13	4x11	3,3	B60089T3805R
89	3 ½	-	3x10	9x13	4x11	3,3	B60089T3805S
102	4	-	3x10	9x14	5x12	3,3	B60102T3805R
102	4	-	3x10	9x14	5x12	3,3	B60102T3805S

R – spherical

S – semi-ballistic

Button bit – DROP CENTER – RETRAC




Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
64	2 ½	-	3x8	9x10	4x9	2,1	B61064T3805R
64	2 ½	-	3x8	9x10	4x9	2,1	B61064T3805S
70	2 ¾	-	3x8	9x11	4x10	2,6	B61070T3805R
70	2 ¾	-	3x8	9x11	4x10	2,6	B61070T3805S
76	3	-	3x9	9x12	4x10	3,4	B61076T3805R
76	3	-	3x9	9x12	4x10	3,4	B61076T3805S
89	3 ½	-	3x10	9x13	4x11	4,9	B61089T3805R
89	3 ½	-	3x10	9x13	4x11	4,9	B61089T3805S
102	4	-	3x10	9x14	5x12	6,7	B61102T3805R
102	4	-	3x10	9x14	5x12	6,7	B61102T3805S

R – spherical

S – semi-ballistic

Button bit – FLAT FACE




Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
64	2 ½	-	3x8	9x10	8x8	1,9	B52064T3805R
64	2 ½	-	3x8	9x10	8x8	1,9	B52064T3805S
76	3	-	3x9	9x12	8x10	2,5	B52076T3805R
76	3	-	3x9	9x12	8x10	2,5	B52076T3805S
89	3 ½	-	3x10	9x13	9x11	3,5	B52089T3805R
89	3 ½	-	3x10	9x13	9x11	3,5	B52089T3805S
102	4	-	3x10	9x14	9x12	4,9	B52102T3805R
102	4	-	3x10	9x14	9x12	4,9	B52102T3805S

R – spherical

S – semi-ballistic

Button bit – FLAT FACE – RETRAC




Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
64	2 ½	-	3x8	9x10	8x8	2,4	B53064T3805R
64	2 ½	-	3x8	9x10	8x8	2,4	B53064T3805S
76	3	-	3x9	9x12	8x10	3,7	B53076T3805R
76	3	-	3x9	9x12	8x10	3,7	B53076T3805S
89	3 ½	-	3x10	9x13	9x11	5,6	B53089T3805R
89	3 ½	-	3x10	9x13	9x11	5,6	B53089T3805S
102	4	-	3x10	9x14	9x12	7,4	B53102T3805R
102	4	-	3x10	9x14	9x12	7,4	B53102T3805S

R – spherical

S – semi-ballistic



Button bit – FLAT FACE – Heavy Duty



Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
64	2 ½	-	2x9	8x11	4x10	1,9	B52064T3815R
70	2 ¾	-	2x9	8x12	4x11	2,3	B52070T3815R
76	3	-	2x10	8x13	4x12	2,5	B52076T3815R
89	3 ½	-	2x11	8x14	5x13	3,6	B52089T3815R
102	4	-	2x11	8x15	6x14	5,0	B52102T3815R

R – spherical



Button bit – FLAT FACE – Heavy Duty - RETRAC



Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
64	2 ½	-	2x9	8x11	4x10	2,4	B53064T3815R
70	2 ¾	-	2x9	8x12	4x11	3,1	B53070T3815R
76	3	-	2x10	8x13	4x12	3,7	B53076T3815R
89	3 ½	-	2x11	8x14	5x13	5,5	B53089T3815R
102	4	-	2x11	8x15	6x14	7,4	B53102T3815R

R – spherical


Button bit



Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
70	2 ¾	-	2x8	8x11	5x10	2,3	B54070T3805R
76	3	-	2x9	8x12	6x11	2,5	B54076T3805R
89	3 ½	-	2x9	8x13	6x12	3,6	B54089T3805R
102	4	-	2x10	8x13	7x12	5,0	B54102T3805R

R – spherical

Reaming button bit



Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
115	4 ½	1x7	3x7	9x13	8x12	6,5	B54115T3815R
127	5	1x7,5	3x7,5	9x14	9x13	7,9	B54127T3815R


R – spherical

Cross X-type bit




Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
64	2 ½	2x7	1x8	-	-	1,9	B48064T380B2
76	3	2x8	1x10	-	-	2,5	B48076T380B2
89	3 ½	2x9	1x10	-	-	3,6	B48089T380B2

Cross X-type bit – RETRAC



Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
76	3	2x7	1x8	-	-	3,7	B49076T380B2
89	3 ½	2x8	1x10	-	-	5,5	B49089T380B2
102	4	2x9	1x10	-	-	7,4	B49102T380B2


Hex rods



Hex		Threads	Length			Weight	Catalogue no.
mm	inch		mm	ft	inch	kg	
32	1 ¼	T38/T38	915	3	-	6,2	21222091
32	1 ¼	T38/T38	1220	4	-	7,9	21222122
32	1 ¼	T38/T38	1525	5	-	9,8	21222152
32	1 ¼	T38/T38	1830	6	-	11,8	21222183
32	1 ¼	T38/T38	2165	7	-	13,9	21222216
32	1 ¼	T38/T38	2435	8	-	15,6	21222243
32	1 ¼	T38/T38	3050	10	-	19,5	21222305
32	1 ¼	T38/T38	3660	12	-	23,4	21222366
32	1 ¼	T38/T38	4265	14	-	27,3	21222427
32	1 ¼	T38/T38	4915	16	-	31,4	21222491
32	1 ¼	T38/T38	5490	18	-	35,1	21222549
32	1 ¼	T38/T38	6100	20	-	39,0	21222610

Flushing hole ϕ 16 mm


Extension rods



Diameter		Threads	Length			Weight	Catalogue no.
mm	inch		mm	ft	inch	kg	
38	1 ½	T38/T38	915	3	-	7,0	23222091
38	1 ½	T38/T38	1220	4	-	9,5	23222122
38	1 ½	T38/T38	1525	5	-	11,9	23222152
38	1 ½	T38/T38	1830	6	-	14,4	23222183
38	1 ½	T38/T38	2165	7	-	17,1	23222216
38	1 ½	T38/T38	2435	8	-	19,3	23222243
38	1 ½	T38/T38	3050	10	-	24,3	23222305
38	1 ½	T38/T38	3660	12	-	29,2	23222366
38	1 ½	T38/T38	4265	14	-	34,1	23222427
38	1 ½	T38/T38	4915	16	-	39,3	23222491
38	1 ½	T38/T38	5490	18	-	44,0	23222549
38	1 ½	T38/T38	6100	20	-	48,9	23222610

Flushing hole ϕ 14,5 mm


Speed rods / M-F rods



Diameter		Threads	Length			Weight	Catalogue no.
mm	inch		mm	ft	inch	kg	
38	1 ½	T38/T38	915	3	-	8,5	26223091
38	1 ½	T38/T38	1220	4	-	10,9	26223122
38	1 ½	T38/T38	1525	5	-	13,4	26223152
38	1 ½	T38/T38	1830	6	-	15,9	26223183
38	1 ½	T38/T38	2165	7	-	18,6	26223216
38	1 ½	T38/T38	2435	8	-	20,7	26223243
38	1 ½	T38/T38	3050	10	-	25,7	26223305
38	1 ½	T38/T38	3660	12	-	30,6	26223366
38	1 ½	T38/T38	4265	14	-	35,5	26223426
38	1 ½	T38/T38	4915	16	-	40,8	26223491
38	1 ½	T38/T38	5490	18	-	45,4	26223549
38	1 ½	T38/T38	6100	20	-	50,4	26223610

Flushing hole ϕ 14,5 mm, Female end ϕ 56 mm


Guide rods / M-F rods



Diameter		Threads	Length			Weight	Catalogue no.
mm	inch		mm	ft	inch	kg	
46	1 ¾	T38/T38	3050	10	-	34,4	266263053
46	1 ¾	T38/T38	3660	12	-	41,2	266263663
46	1 ¾	T38/T38	4265	14	-	48,0	266264263


Flushing hole ϕ 17 mm, Female end ϕ 56 mm

Guide tube rods




Diameter		Threads	Length			Weight	Catalogue no.
mm	inch		mm	ft	inch	kg	
56	2 ¼	T38/T38	1525	5	-	18,7	1256T38T38152
56	2 ¼	T38/T38	1830	6	-	22,2	1256T38T38183
56	2 ¼	T38/T38	3050	10	-	36,0	1256T38T38305
56	2 ¼	T38/T38	3660	12	-	42,9	1256T38T38366
64	2 ½	T38/T38	3660	12	-	49,4	1264T38T38366

Guide tube rods




Diameter		Threads	Length			Weight	Catalogue no.
mm	inch		mm	ft	inch	kg	
56	2 ¼	T38/T38	1525	5	-	19,5	1356T38T38152
56	2 ¼	T38/T38	1830	6	-	23,0	1356T38T38183
56	2 ¼	T38/T38	3050	10	-	36,8	1356T38T38305
56	2 ¼	T38/T38	3660	12	-	43,7	1356T38T38366
64	2 ½	T38/T38	3660	12	-	52,4	1364T38T38366

Coupling sleeve




Diameter		Threads	Length		Weight	Catalogue no.
mm	inch		mm	inch	kg	
55	2 ¼	T38/T38	180	7 ¾	2,0	3922200

Full bridge



Diameter		Threads	Length		Weight	Catalogue no.
mm	inch		mm	inch	kg	
55	2 ¼	T38/R32	185	7	2,3	3947201
55	2 ¼	T38/T38	210	8 ¼	2,6	3922201

M-F adapters




Threads	Length		Weight	Catalogue no.
female/male	mm	inch	kg	
T38/R32	240	9 ½	2,4	39472061
T38/T45	275	10 ¾	3,2	3922306


M-M adapters



Threads	Length		Weight	Catalogue no.
male/male	mm	inch	kg	
T38/T38	220	8 ¾	1,6	3838T38T3800



Button bit – DROP CENTER




Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
70	2 ¾	-	4x8	8x11	5x10	2,4	B50070T4505R
70	2 ¾	-	4x8	8x11	5x10	2,4	B50070T4505S
76	3	-	4x8	8x12	5x11	2,8	B50076T4505R
76	3	-	4x8	8x12	5x11	2,8	B50076T4505S
89	3 ½	-	4x9	8x13	5x12	3,2	B50089T4505R
89	3 ½	-	4x9	8x13	5x12	3,2	B50089T4505S
102	4	-	4x9	8x14	6x13	4,5	B50102T4505R
102	4	-	4x9	8x14	6x13	4,5	B50102T4505S
115	4 ½	-	4x9	8x15	6x14	6,2	B50115T4505R
115	4 ½	-	4x9	8x15	6x14	6,2	B50115T4505S
127	5	-	4x10	8x15	8x14	7,3	B50127T4505R
127	5	-	4x10	8x14	8x14	7,3	B50127T4505S

R – spherical

S – semi-ballistic

Button bit – DROP CENTER – RETRAC




Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
70	2 ¾	-	4x8	8x11	5x10	2,6	B51070T4505R
70	2 ¾	-	4x8	8x11	5x10	2,6	B51070T4505S
76	3	-	4x8	8x12	5x11	3,4	B51076T4505R
76	3	-	4x8	8x12	5x11	3,4	B51076T4505S
89	3 ½	-	4x9	8x13	5x12	5,2	B51089T4505R
89	3 ½	-	4x9	8x13	5x12	5,2	B51089T4505S
102	4	-	4x9	8x14	6x13	7,0	B51102T4505R
102	4	-	4x9	8x14	6x13	7,0	B51102T4505S
115	4 ½	-	4x9	8x15	6x14	9,3	B51115T4505R
115	4 ½	-	4x9	8x15	6x14	9,3	B51115T4505S
127	5	-	4x10	8x15	8x14	11,5	B51127T4505R
127	5	-	4x10	8x15	8x14	11,5	B51127T4505S

R – spherical

S – semi-ballistic

Button bit – DROP CENTER




Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
70	2 ¾	-	3x9	9x11	4x10	2,3	B60070T4505R
70	2 ¾	-	3x9	9x11	4x10	2,3	B60070T4505S
76	3	-	3x9	9x12	4x10	2,7	B60076T4505R
76	3	-	3x9	9x12	4x10	2,7	B60076T4505S
89	3 ½	-	3x10	9x13	4x11	3,2	B60089T4505R
89	3 ½	-	3x10	9x13	4x11	3,2	B60089T4505S
102	4	-	3x10	9x14	5x12	4,3	B60102T4505R
102	4	-	3x10	9x14	5x12	4,3	B60102T4505S
115	4 ½	-	3x10	9x15	5x13	6,0	B60115T4505R
115	4 ½	-	3x10	9x15	5x13	6,0	B60115T4505S
127	5	-	3x10	9x16	5x14	7,1	B60127T4505R
127	5	-	3x10	9x16	5x14	7,1	B60127T4505S

R – spherical

S – semi-ballistic

Button bit – DROP CENTER – RETRAC




Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
70	2 ¾	-	3x9	9x11	4x10	2,8	B61070T4505R
70	2 ¾	-	3x9	9x11	4x10	2,8	B61070T4505S
76	3	-	3x9	9x12	4x10	3,4	B61076T4505R
76	3	-	3x9	9x12	4x10	3,4	B61076T4505S
89	3 ½	-	3x10	9x13	4x11	5,3	B61089T4505R
89	3 ½	-	3x10	9x13	4x11	5,3	B61089T4505S
102	4	-	3x10	9x14	5x12	6,9	B61102T4505R
102	4	-	3x10	9x14	5x12	6,9	B61102T4505S
115	4 ½	-	3x10	9x15	5x13	8,8	B61115T4505R
115	4 ½	-	3x10	9x15	5x13	8,8	B61115T4505S
127	5	-	3x10	9x16	5x14	10,2	B61127T4505R
127	5	-	3x10	9x16	5x14	10,2	B61127T4505S

R – spherical

S – semi-ballistic

Button bit – FLAT FACE




Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
76	3	-	3x9	9x12	8x10	2,8	B52076T4505R
76	3	-	3x9	9x12	8x10	2,8	B52076T4505S
80	3 5/32	-	3x9	9x12	8x10	3,0	B52080T4505R
80	3 5/32	-	3x9	9x12	8x10	3,0	B52080T4505S
89	3 ½	-	3x10	9x13	9x11	3,3	B52089T4505R
89	3 ½	-	3x10	9x13	9x11	3,3	B52089T4505S
102	4	-	3x10	9x14	9x12	4,6	B52102T4505R
102	4	-	3x10	9x14	9x12	4,6	B52102T4505S
115	4 ½	-	3x10	9x15	10x13	6,5	B52115T4505R
115	4 ½	-	3x10	9x15	10x13	6,5	B52115T4505S

R – spherical

S – semi-ballistic

Button bit – FLAT FACE – RETRAC




Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
76	3	-	3x9	9x12	8x10	3,5	B53076T4505R
76	3	-	3x9	9x12	8x10	3,5	B53076T4505S
80	3 ⁵ / ₃₂	-	3x9	9x12	8x10	4,2	B53080T4505R
80	3 ⁵ / ₃₂	-	3x9	9x12	8x10	4,2	B53080T4505S
89	3 ½	-	3x10	9x13	9x11	5,4	B53089T4505R
89	3 ½	-	3x10	9x13	9x11	5,4	B53089T4505S
102	4	-	3x10	9x14	9x12	7,2	B53102T4505R
102	4	-	3x10	9x14	9x12	7,2	B53102T4505S
115	4 ½	-	3x10	9x15	10x13	8,4	B53115T4505R
115	4 ½	-	3x10	9x15	10x13	8,4	B53115T4505S

R – spherical

S – semi-ballistic


Button bit – FLAT FACE – Heavy Duty



Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
70	2 ¾	-	2x9	8x12	4x11	2,4	B52070T4515R
76	3	-	2x10	8x13	4x12	2,8	B52076T4515R
80	3 ⁵ / ₃₂	-	2x11	8x13	5x12	3,0	B52080T4515R
89	3 ½	-	2x11	8x14	5x13	3,3	B52089T4515R
102	4	-	2x11	8x15	6x14	4,6	B52102T4515R
115	4 ½	-	2x12	8x16	7x15	6,5	B52115T4515R

R – spherical


Button bit – FLAT FACE – RETRAC – Heavy Duty



Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
70	2 ¾	-	2x9	8x12	4x11	3,2	B53070T4515R
76	3	-	2x10	8x13	4x12	3,5	B53076T4515R
80	3 5/32	-	2x11	8x13	5x12	4,2	B53080T4515R
89	3 ½	-	2x11	8x14	5x13	5,4	B53089T4515R
102	4	-	2x11	8x15	6x14	7,2	B53102T4515R
115	4 ½	-	2x12	8x15	7x14	8,4	B53115T4515R


R – spherical

Button bit – DROP CENTER – RETRAC



Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
70	2 ¾	2x10	1x10	6x14	4x9	3,1	57703253D
76	3	2x10	1x10	6x14	4x9	3,7	57763253D


Button bit



Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
76	3	-	2x10	8x12	6x11	2,8	B54076T4505R
89	3 ½	-	2x10	8x13	6x12	3,4	B54089T4505R
102	4	-	2x11	8x13	7x12	4,7	B54102T4505R
115	4 ½	-	2x12	8x14	8x13	6,6	B54115T4505R

R – spherical

Reaming button bit



Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
115	4 ½	1x8	3x8	9x13	8x12	6,6	B54115T4515R
127	5	1x9	3x9	9x14	9x13	8,1	B54127T4515R
152	6	1x10	3x10	9x15	11x14	11,2	B54152T4515R


R – spherical

Cross X-type bit




Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
76	3	2x9	1x10	-	-	2,7	B48076T450B2
89	3 ½	2x10	1x10	-	-	3,3	B48089T450B2
102	4	2x10	1x11	-	-	4,7	B48102T450B2

Cross X-type bit – RETRAC



Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
76	3	2x9	1x10	-	-	3,5	B49076T450B2
89	3 ½	2x10	1x10	-	-	4,7	B49089T450B2
102	4	2x10	1x11	-	-	6,8	B49102T450B2


Extension rods diameter 38mm



Diameter		Threads	Length			Weight	Catalogue no.
mm	inch		mm	ft	inch	kg	
38	1 ½	T45/T45	915	3	-	8,1	23323091
38	1 ½	T45/T45	1220	4	-	10,7	23323122
38	1 ½	T45/T45	1525	5	-	13,4	23323152
38	1 ½	T45/T45	1830	6	-	16,1	23323183
38	1 ½	T45/T45	2165	7	-	19,0	23323216
38	1 ½	T45/T45	2435	8	-	21,3	23323243
38	1 ½	T45/T45	3050	10	-	26,7	23323305
38	1 ½	T45/T45	3660	12	-	32,0	23323366
38	1 ½	T45/T45	4265	14	-	37,3	23323427
38	1 ½	T45/T45	4915	16	-	43,0	23323491
38	1 ½	T45/T45	5490	18	-	48,0	23323549
38	1 ½	T45/T45	6100	20	-	53,3	23323610

Flushing hole ϕ 14,5 mm


Extension rods diameter 46mm



Diameter		Threads	Length			Weight	Catalogue no.
mm	inch		mm	ft	inch	kg	
46	1 ¾	T45/T45	915	3	-	9,6	18323091
46	1 ¾	T45/T45	1220	4	-	13,0	18323122
46	1 ¾	T45/T45	1525	5	-	16,4	18323152
46	1 ¾	T45/T45	1830	6	-	19,8	18323183
46	1 ¾	T45/T45	2165	7	-	23,5	18323216
46	1 ¾	T45/T45	2435	8	-	26,5	18323243
46	1 ¾	T45/T45	3050	10	-	33,4	18323305
46	1 ¾	T45/T45	3660	12	-	40,2	18323366
46	1 ¾	T45/T45	4265	14	-	46,9	18323427
46	1 ¾	T45/T45	4915	16	-	54,2	18323491
46	1 ¾	T45/T45	6100	20	-	67,4	18323610
46	1 ¾	T45/T45	7200	24	-	79,7	18323720

Flushing hole ϕ 17 mm


Speed rods / M-F rods



Diameter		Threads	Length			Weight	Catalogue no.
mm	inch		mm	ft	inch	kg	
46	1 ¾	T45/T45	1525	5	-	18,3	26626152
46	1 ¾	T45/T45	1830	6	-	21,7	26626183
46	1 ¾	T45/T45	2165	7	-	25,4	26626216
46	1 ¾	T45/T45	2435	8	-	28,5	26626243
46	1 ¾	T45/T45	3050	10	-	35,3	26626305
46	1 ¾	T45/T45	3660	12	-	42,1	26626366
46	1 ¾	T45/T45	4265	14	-	48,8	26626426
46	1 ¾	T45/T45	4915	16	-	56,1	26626491
46	1 ¾	T45/T45	6100	20	-	69,3	26626610
46	1 ¾	T45/T45	7200	24	-	81,6	26626720

Flushing hole ϕ 17 mm, Female end ϕ 67 mm


Guide rods / M-F rods



Diameter		Threads	Length			Weight	Catalogue no.
mm	inch		mm	ft	inch	kg	
52	2	T45/T45	3050	10	-	43,3	269293053
52	2	T45/T45	3660	12	-	51,7	269293663
52	2	T45/T45	4265	14	-	60,1	269294263


Flushing hole ϕ 21,5 mm, Female end ϕ 67 mm

Guide tube rods




Diameter		Threads	Length			Weight	Catalogue no.
mm	inch		mm	ft	inch	kg	
63	2 ½	T45/T45	1830	6	-	25,9	1263T45T45183
63	2 ½	T45/T45	3660	12	-	49,7	1263T45T45366
64	2 ½	T45/T45	4265	14	-	57,6	1263T45T45426
76	3	T45/T45	3660	12	-	72,2	1276T45T45366
76	3	T45/T45	4265	14	-	83,6	1276T45T45426

Guide tube rods




Diameter		Threads	Length			Weight	Catalogue no.
mm	inch		mm	ft	inch	kg	
63	2 ½	T45/T45	1830	6	-	26,9	1363T45T45183
63	2 ½	T45/T45	3660	12	-	50,7	1363T45T45366
63	2 ½	T45/T45	4265	14	-	58,6	1363T45T45426
76	3	T45/T45	3660	12	-	74,9	1376T45T45366
76	3	T45/T45	4265	14	-	86,3	1376T45T45426

Coupling sleeve




Diameter		Threads	Length		Weight	Catalogue no.
mm	inch		mm	inch	kg	
64	2 ½	T45/T38	180	7 ³⁄₃₂	2,9	3922300
64	2 ½	T45/T45	180	7 ³⁄₃₂	2,5	3932300

Full bridge



Diameter		Threads	Length		Weight	Catalogue no.
mm	inch		mm	inch	kg	
64	2 ½	T45/T45	210	8 ¼	3,0	3932301

M-F adapters




Threads	Length		Weight	Catalogue no.
female/male	mm	inch	kg	
T45/T38	235	10 ⅜	3,2	3932206
T45/T51	275	10 ⅞	3,8	39523065


M-M adapters



Threads	Length		Weight	Catalogue no.
male/male	mm	inch	kg	
T45/T45	220	8 ¾	2,4	3845T45T4500



Button bit – DROP CENTER




Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
89	3 ½	-	4x9	8x13	5x12	3,5	B50089T5105R
89	3 ½	-	4x9	8x13	5x12	3,5	B50089T5105S
102	4	-	4x10	8x14	6x13	5,0	B50102T5105R
102	4	-	4x10	8x14	6x13	5,0	B50102T5105S
115	4 ½	-	4x11	8x15	6x14	7,3	B50115T5105R
115	4 ½	-	4x11	8x15	6x14	7,3	B50115T5105S
127	5	-	4x11	8x16	8x15	7,8	B50127T5105R
127	5	-	4x11	8x16	8x15	7,8	B50127T5105S
152	6	-	4x12	8x17	4x15, 4x16	12,2	B50152T5105R
152	6	-	4x12	8x17	4x15, 4x16	12,2	B50152T5105S

R – spherical

S – semi-ballistic

Button bit – DROP CENTER – RETRAC



Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
89	3 ½	-	4x9	8x13	5x12	5,2	B51089T5105R
89	3 ½	-	4x9	8x13	5x12	5,2	B51089T5105S
102	4	-	4x10	8x14	6x13	7,0	B51102T5105R
102	4	-	4x10	8x14	6x13	7,0	B51102T5105S
115	4 ½	-	4x11	8x15	6x14	9,4	B51115T5105R
115	4 ½	-	4x11	8x15	6x14	9,4	B51115T5105S
127	5	-	4x11	8x16	8x15	11,8	B51127T5105R
127	5	-	4x11	8x16	8x15	11,8	B51127T5105S
152	6	-	4x12	8x17	4x15, 4x16	19,0	B51152T5105R
152	6	-	4x12	8x17	4x15, 4x16	19,0	B51152T5105S

R – spherical

S – semi-ballistic

Button bit – DROP CENTER




Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
89	3 ½	-	3x11	9x13	4x11	3,5	B60089T5105R
89	3 ½	-	3x11	9x13	4x11	3,5	B60089T5105S
102	4	-	3x12	9x14	5x12	4,5	B60102T5105R
102	4	-	3x12	9x14	5x12	4,5	B60102T5105S
115	4 ½	-	3x12	9x15	5x13	6,5	B60115T5105R
115	4 ½	-	3x12	9x15	5x13	6,5	B60115T5105S
127	5	-	3x13	9x16	5x14	8,1	B60127T5105R
127	5	-	3x13	9x16	5x14	8,1	B60127T5105S

R – spherical

S – semi-ballistic

Button bit – DROP CENTER – RETRAC




Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
89	3 ½	-	3x11	9x13	4x11	6,6	B61089T5105R
89	3 ½	-	3x11	9x13	4x11	6,6	B61089T5105S
102	4	-	3x12	9x14	5x12	9,1	B61102T5105R
102	4	-	3x12	9x14	5x12	9,1	B61102T5105S
115	4 ½	-	3x12	9x15	5x13	10,2	B61115T5105R
115	4 ½	-	3x12	9x15	5x13	10,2	B61115T5105S
127	5	-	3x13	9x16	5x14	13,8	B61127T5105R
127	5	-	3x13	9x16	5x14	13,8	B61127T5105S

R – spherical

S – semi-ballistic

Button bit – FLAT FACE




Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
80	3 5/32	-	3x10	9x12	8x10	3,1	B52080T5105R
80	3 5/32	-	3x10	9x12	8x10	3,1	B52080T5105S
89	3 ½	-	3x11	9x13	8x11	3,6	B52089T5105R
89	3 ½	-	3x11	9x13	8x11	3,6	B52089T5105S
102	4	-	3x12	9x14	9x12	4,6	B52102T5105R
102	4	-	3x12	9x14	9x12	4,6	B52102T5105S
115	4 ½	-	3x12	9x15	10x13	6,7	B52115T5105R
115	4 ½	-	3x12	9x15	10x13	6,7	B52115T5105S
127	5	-	3x13	9x16	10x14	8,4	B52127T5105R
127	5	-	3x13	9x16	10x14	8,4	B52127T5105S
152	6	-	3x14	9x16	10x14	12,1	B52152T5105R
152	6	-	3x14	9x16	10x14	12,1	B52152T5105S

R – spherical

S – semi-ballistic

Button bit – FLAT FACE – RETRAC




Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
80	3 5/32	-	3x10	9x12	8x10	4,0	B53080T5105R
80	3 5/32	-	3x10	9x12	8x10	4,0	B53080T5105S
89	3 1/2	-	3x11	9x13	9x11	4,9	B53089T5105R
89	3 1/2	-	3x11	9x13	9x11	4,9	B53089T5105S
102	4	-	3x12	9x14	9x12	6,8	B53102T5105R
102	4	-	3x12	9x14	9x12	6,8	B53102T5105S
115	4 1/2	-	3x12	9x15	10x13	8,8	B53115T5105R
115	4 1/2	-	3x12	9x15	10x13	8,8	B53115T5105S
127	5	-	3x13	9x16	10x14	12,0	B53127T5105R
127	5	-	3x13	9x16	10x14	12,0	B53127T5105S
152	6	-	3x14	9x16	10x14	19,2	B53152T5105R
152	6	-	3x14	9x16	10x14	19,2	B53152T5105S

R – spherical

S – semi-ballistic


Button bit – FLAT FACE – Heavy Duty



Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
80	3 5/32	-	2x12	8x13	5x12	3,1	B52080T5115R
89	3 1/2	-	2x13	8x14	5x13	3,6	B52089T5115R
102	4	-	2x13	8x15	6x14	4,6	B52102T5115R
115	4 1/2	-	2x14	8x16	7x15	6,7	B52115T5115R
127	5	-	2x14	8x17	8x16	8,4	B52127T5115R

R – spherical


Button bit – FLAT FACE – RETRAC – Heavy Duty



Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
80	3 5/32	-	2x12	8x13	5x12	4,0	B53080T5115R
89	3 1/2	-	2x13	8x14	5x13	4,9	B53089T5115R
102	4	-	2x13	8x15	6x14	6,8	B53102T5115R
115	4 1/2	-	2x14	8x16	7x15	8,8	B53115T5115R
127	5	-	2x14	8x17	8x16	12,0	B53127T5115R

R – spherical


Button bit



Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
89	3 1/2	-	2x12	8x13	6x12	3,6	B54089T5105R
102	4	-	2x13	8x13	7x13	4,6	B54102T5105R
115	4 1/2	-	2x13	8x14	8x13	6,7	B54115T5105R
127	5	-	2x14	8x15	8x14	8,4	B54127T5105R

R – spherical


Reaming button bit



Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
115	4 ½	1x9	3x9	9x13	8x12	6,7	B54115T5115R
127	5	1x10	3x10	9x14	9x13	8,4	B54127T5115R
152	6	1x11	3x11	9x15	11x14	12,1	B54152T5115R


R – spherical

Cross bit – RETRAC



Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
102	4	–	1x16	-	3x13	5,8	B47102T511B2
115	4 ½	–	1x16	-	3x13	7,3	B47115T511B2
127	5	–	1x16	-	3x14	9,8	B47127T511B2
140	5 ½	–	1x16	-	3x14	12,7	B47140T511B2
152	6	–	1x16	-	3x14	15,3	B47152T511B2


Extension rods



Diameter		Threads	Length			Weight	Catalogue no.
mm	inch		mm	ft	inch	kg	
52	2	T51/T51	915	3	-	11,8	28050091
52	2	T51/T51	1220	4	-	16,1	28050122
52	2	T51/T51	1525	5	-	20,3	28050152
52	2	T51/T51	1830	6	-	24,5	28050183
52	2	T51/T51	2165	7	-	29,2	28050216
52	2	T51/T51	2435	8	-	32,9	28050243
52	2	T51/T51	3050	10	-	41,4	28050305
52	2	T51/T51	3660	12	-	49,9	28050366
52	2	T51/T51	4265	14	-	58,2	28050427
52	2	T51/T51	4915	16	-	67,2	28050491
52	2	T51/T51	6100	20	-	83,7	28050610
52	2	T51/T51	7200	24	-	98,9	28050720

Flushing hole ϕ 21,5 mm


Speed rods / M-F rods



Diameter		Threads	Length			Weight	Catalogue no.
mm	inch		mm	ft	inch	kg	
52	2	T51/T51	1525	5	-	23,5	26929152
52	2	T51/T51	1830	6	-	27,5	26929183
52	2	T51/T51	2165	7	-	32,4	26929216
52	2	T51/T51	2435	8	-	36,1	26929243
52	2	T51/T51	3050	10	-	44,6	26929305
52	2	T51/T51	3660	12	-	53,1	26929366
52	2	T51/T51	4265	14	-	61,5	26929427
52	2	T51/T51	4915	16	-	70,5	26929491
52	2	T51/T51	6100	20	-	86,9	26929610
52	2	T51/T51	7200	24	-	102,1	26929720

Flushing hole ϕ 21,5 mm, Female end ϕ 74 mm


Guide rods / M-F rods



Diameter		Threads	Length			Weight	Catalogue no.
mm	inch		mm	ft	inch	kg	
60	2 ¾	T51/T51	3660	12	-	70,7	269693663
60	2 ¾	T51/T51	4265	14	-	82,3	269694263


Flushing hole ϕ 22,6 mm, Female end ϕ 74 mm

Guide tube rods




Diameter		Threads	Length			Weight	Catalogue no.
mm	inch		mm	ft	inch	kg	
76	3	T51/T51	1830	6	-	37,2	1276T51T51183
76	3	T51/T51	3660	12	-	71,8	1276T51T51366
76	3	T51/T51	4265	14	-	83,2	1276T51T51426
87	3 ½	T51/T51	3660	12	-	95,7	1287T51T51366
87	3 ½	T51/T51	4265	14	-	110,9	1287T51T51426

Guide tube rods




Diameter		Threads	Length			Weight	Catalogue no.
mm	inch		mm	ft	inch	kg	
76	3	T51/T51	1830	6	-	39,4	1376T51T51183
76	3	T51/T51	3660	12	-	74,0	1376T51T51366
76	3	T51/T51	4265	14	-	85,4	1376T51T51426
87	3 ½	T51/T51	3660	12	-	100,7	1387T51T51366
87	3 ½	T51/T51	4265	14	-	115,9	1387T51T51426

Coupling sleeve




Diameter		Threads	Length		Weight	Catalogue no.
mm	inch		mm	inch	kg	
72	2 ¾	T51/T51	210	8 ⅝ ₃₂	4,0	3952532
74	3	T51/T45	195	7 ⅞ ₁₆	4,2	3952300
74	3	T51/T51	210	8 ⅝ ₃₂	4,7	3952500

Full bridge



Diameter		Threads	Length		Weight	Catalogue no.
mm	inch		mm	inch	kg	
76	3	T51/T45	225	8 ⅞ ₈	5,6	3952301
76	3	T51/T51	240	9 ½	5,7	3952501

M-F adapters




Threads female/male	Length		Weight	Catalogue no.
	mm	inch	kg	
T51/T45	300	11 ¾	5,0	3952306
T51/GT60	300	11 ¾	7,5	3954606


M-M adapters




Threads male/male	Length		Weight	Catalogue no.
	mm	inch	kg	
T51/T51	250	9 7/8	3,2	3851T51T5100




Button bit – DROP CENTER



Button bit – FLAT FACE




Button bit – FLAT FACE – Heavy Duty




Diameter		Flushing holes (mm)		Buttons (mm)		Weight kg	Catalogue no.
		Side No x Size	Front No x Size	Gauge No x Size	Front No x Size		
89	3 ½	-	4 x 10	8 x 13	5 x 12	3,7	D60089ST5805R
89	3 ½	-	4 x 10	8 x 13	5 x 12	3,7	D60089ST5805S
102	4	-	4 x 11	8 x 14	6 x 13	5,2	D60102ST5805R
102	4	-	4 x 11	8 x 14	6 x 13	5,2	D60102ST5805S
115	4 ½	-	4 x 11	8 x 16	6 x 15	7,6	D60115ST5805R
115	4 ½	-	4 x 11	8 x 16	6 x 15	7,6	D60115ST5805S
127	5	-	4 x 12	8 x 16	8 x 15	8,1	D60127ST5805R
127	5	-	4 x 12	8 x 16	8 x 15	8,1	D60127ST5805S
89	3 ½	-	3 x 11	9 x 12	9 x 11	3,7	D62089ST5805R
89	3 ½	-	3 x 11	9 x 12	9 x 11	3,7	D62089ST5805S
102	4	-	3 x 12	9 x 13	9 x 12	5,3	D62102ST5805R
102	4	-	3 x 12	9 x 13	9 x 12	5,3	D62102ST5805S
115	4 ½	-	3 x 12	9 x 14	10 x 12	7,7	D62115ST5805R
115	4 ½	-	3 x 12	9 x 14	10 x 12	7,7	D62115ST5805S
127	5	-	3 x 13	9 x 16	10 x 14	8,2	D62127ST5805R
127	5	-	3 x 13	9 x 16	10 x 14	8,2	D62127ST5805S
89	3 ½	-	2 x 14	8 x 14	5 x 12	3,7	D62089ST5815R
102	4	-	2 x 14	8 x 15	6 x 13	5,3	D62102ST5815R
115	4 ½	-	2 x 15	8 x 16	7 x 14	7,7	D62115ST5815R
127	5	-	2 x 15	8 x 17	8 x 15	8,2	D62127ST5815R


Button bit – DROP CENTER – RETRAC



Button bit – FLAT FACE – RETRAC




Button bit – FLAT FACE – RETRAC – Heavy Duty



Diameter		Flushing holes (mm)		Buttons (mm)		Weight kg	Catalogue no.
		Side No x Size	Front No x Size	Gauge No x Size	Front No x Size		
89	3 ½	-	4 x 10	8 x 13	5 x 12	4,3	D61089ST5805R
89	3 ½	-	4 x 10	8 x 13	5 x 12	4,3	D61089ST5805S
102	4	-	4 x 11	8 x 14	6 x 13	6,2	D61102ST5805R
102	4	-	4 x 11	8 x 14	6 x 13	6,2	D61102ST5805S
115	4 ½	-	4 x 11	8 x 16	6 x 15	8,7	D61115ST5805R
115	4 ½	-	4 x 11	8 x 16	6 x 15	8,7	D61115ST5805S
127	5	-	4 x 12	8 x 16	8 x 15	10,4	D61127ST5805R
127	5	-	4 x 12	8 x 16	8 x 15	10,4	D61127ST5805S
89	3 ½	-	3 x 11	9 x 12	9 x 11	4,3	D63089ST5805R
89	3 ½	-	3 x 11	9 x 12	9 x 11	4,3	D63089ST5805S
102	4	-	3 x 12	9 x 13	9 x 12	6,2	D63102ST5805R
102	4	-	3 x 12	9 x 13	9 x 12	6,2	D63102ST5805S
115	4 ½	-	3 x 12	9 x 14	10 x 12	8,7	D63115ST5805R
115	4 ½	-	3 x 12	9 x 14	10 x 12	8,7	D63115ST5805S
127	5	-	3 x 13	9 x 16	10 x 14	10,4	D63127ST5805R
127	5	-	3 x 13	9 x 16	10 x 14	10,4	D63127ST5805S
89	3 ½	-	2 x 14	8 x 14	5 x 12	4,3	D63089ST5815R
102	4	-	2 x 14	8 x 15	6 x 13	6,2	D63102ST5815R
115	4 ½	-	2 x 15	8 x 16	7 x 14	8,7	D63115ST5815R
127	5	-	2 x 15	8 x 17	8 x 15	10,4	D63127ST5815R


MF rod




Round		Threads	Length			Weight	Catalogue no.
mm	inch		mm	ft	inch	kg	
60	2 3/8	ST58/ST58	3660	12	-	76,2	11R60ST58ST58366
60	2 3/8	ST58/ST58	4265	14	-	86,7	11R60ST58ST58426
60	2 3/8	ST58/ST58	5490	18	-	109,6	11R60ST58ST58549
60	2 3/8	ST58/ST58	6095	20	-	121,7	11R60ST58ST58609

Flushing hole ϕ 22,6 mm, Female end ϕ 81 mm


Bit adapter coupling



Threads		D		Length		Weight	Catalogue no.
A	B	mm	inch	mm	inch	kg	
T51	ST58	76	3	285	11 7/32	5,7	3922506
ST58	T51	81	3 1/16	310	12 3/16	6,1	3952206
ST58	GT60	82	3 15/64	310	12 3/16	6,1	3952606



Button bit – DROP CENTER




Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
92	3 5/8	-	4x11	8x14	5x13	4,3	B50092G6005R
92	3 5/8	-	4x11	8x14	5x13	4,3	B50092G6005S
96	3 3/4	-	4x11	8x14	6x13	4,8	B50096G6005R
96	3 3/4	-	4x11	8x14	6x13	4,8	B50096G6005S
102	4	-	4x12	8x14	6x13	5,2	B50102G6005R
102	4	-	4x12	8x14	6x13	5,2	B50102G6005S
115	4 1/2	-	4x12	8x15	6x14	7,5	B50115G6005R
115	4 1/2	-	4x12	8x15	6x14	7,5	B50115G6005S
127	5	-	4x13	8x16	8x15	8,7	B50127G6005R
127	5	-	4x13	8x16	8x15	8,7	B50127G6005S
140	5 1/2	-	4x13	8x16	8x15	10,4	B50140G6005R
140	5 1/2	-	4x13	8x16	8x15	10,4	B50140G6005S

R – spherical

S – semi-ballistic

Button bit – DROP CENTER – RETRAC




Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
92	3 5/8	-	4x11	8x13	5x12	6,0	B51092G6005R
92	3 5/8	-	4x11	8x13	5x12	6,0	B51092G6005S
96	3 3/4	-	4x11	8x14	6x13	6,9	B51096G6005R
96	3 3/4	-	4x11	8x14	6x13	6,9	B51096G6005S
102	4	-	4x12	8x14	6x13	7,8	B51102G6005R
102	4	-	4x12	8x14	6x13	7,8	B51102G6005S
115	4 1/2	-	4x12	8x15	6x14	10,8	B51115G6005R
115	4 1/2	-	4x12	8x15	6x14	10,8	B51115G6005S
127	5	-	4x13	8x16	8x15	13,7	B51127G6005R
127	5	-	4x13	8x16	8x15	13,7	B51127G6005S
140	5 1/2	-	4x13	8x16	8x15	17,7	B51140G6005R
140	5 1/2	-	4x13	8x16	8x15	17,7	B51140G6005S

R – spherical

S – semi-ballistic

Button bit – FLAT FACE




Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
102	4	-	3x14	9x14	9x12	5,5	B52102G6005R
102	4	-	3x14	9x14	9x12	5,5	B52102G6005S
115	4 1/2	-	3x14	9x15	10x13	7,7	B52115G6005R
115	4 1/2	-	3x14	9x15	10x13	7,7	B52115G6005S
127	5	-	3x14	9x16	10x14	9,0	B52127G6005R
127	5	-	3x14	9x16	10x14	9,0	B52127G6005S
140	5 1/2	-	3x14	9x16	10x15	11,5	B52140G6005R
140	5 1/2	-	3x14	9x16	10x15	11,5	B52140G6005S
152	6	-	3x14	9x16	10x15	13,1	B52152G6005R
152	6	-	3x14	9x16	10x15	13,1	B52152G6005S

R – spherical

S – semi-ballistic

Button bit – FLAT FACE – RETRAC




Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
102	4	-	3x14	9x14	9x12	8,0	B53102G6005R
102	4	-	3x14	9x14	9x12	8,0	B53102G6005S
115	4 ½	-	3x14	9x15	10x13	11,1	B53115G6005R
115	4 ½	-	3x14	9x15	10x13	11,1	B53115G6005S
127	5	-	3x14	9x16	10x14	14,7	B53127G6005R
127	5	-	3x14	9x16	10x14	14,7	B53127G6005S
140	5 ½	-	3x14	9x16	10x15	18,6	B53140G6005R
140	5 ½	-	3x14	9x16	10x15	18,6	B53140G6005S
152	6	-	3x14	9x16	10x15	20,7	B53152G6005R
152	6	-	3x14	9x16	10x15	20,7	B53152G6005S

R – spherical

S – semi-ballistic


Button bit – FLAT FACE – Heavy Duty



Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
102	4	-	2x15	8x15	6x14	5,5	B52102G6015R
115	4 ½	-	2x16	8x16	7x15	7,7	B52115G6015R
127	5	-	2x16	8x17	8x15	9,0	B52127G6015R
140	5 ½	-	2x17	8x17	9x16	11,5	B52140G6015R
152	6	-	2x17	8x17	9x16	13,1	B52152G6015R

R – spherical


Button bit – FLAT FACE – RETRAC - Heavy Duty



Diameter		Flushing holes		Buttons (mm)		Weight	Catalogue no.
mm	inch	Side No x Size	Front No x Size	Gauge No x Size	Front No x Size	kg	
102	4	-	2x15	8x15	6x14	8,0	B53102G6015R
115	4 ½	-	2x16	8x16	7x15	11,1	B53115G6015R
127	5	-	2x16	8x17	8x15	14,7	B53127G6015R
140	5 ½	-	2x17	8x17	9x16	18,6	B53140G6015R
152	6	-	2x17	8x17	9x16	20,7	B53152G6015R

R – spherical


Extension rods



Diameter		Threads	Length			Weight	Catalogue no.
mm	inch		mm	ft	inch	kg	
60	2 3/8	GT60/GT60	1830	6	-	33,7	10R60G60G60183
60	2 3/8	GT60/GT60	2165	7	-	40,0	10R60G60G60216
60	2 3/8	GT60/GT60	2435	8	-	45,2	10R60G60G60243
60	2 3/8	GT60/GT60	3050	10	-	56,9	10R60G60G60305
60	2 3/8	GT60/GT60	3660	12	-	68,5	10R60G60G60366
60	2 3/8	GT60/GT60	4265	14	-	80,0	10R60G60G60426
60	2 3/8	GT60/GT60	4915	16	-	92,4	10R60G60G60491
60	2 3/8	GT60/GT60	5470	18	-	103,0	10R60G60G60547
60	2 3/8	GT60/GT60	6100	20	-	115,0	10R60G60G60610

Flushing hole ϕ 22,6 mm


Speed rods / M-F rods



Diameter		Threads	Length			Weight	Catalogue no.
mm	inch		mm	ft	inch	kg	
60	2 3/8	GT60/GT60	1830	6	-	35,5	11R60G60G60183
60	2 3/8	GT60/GT60	2165	7	-	45,9	11R60G60G60216
60	2 3/8	GT60/GT60	2435	8	-	51,0	11R60G60G60243
60	2 3/8	GT60/GT60	3050	10	-	62,7	11R60G60G60305
60	2 3/8	GT60/GT60	3660	12	-	74,3	11R60G60G60366
60	2 3/8	GT60/GT60	4265	14	-	85,9	11R60G60G60426
60	2 3/8	GT60/GT60	4915	16	-	98,2	11R60G60G60491
60	2 3/8	GT60/GT60	5470	18	-	108,8	11R60G60G60547
60	2 3/8	GT60/GT60	6100	20	-	120,8	11R60G60G60610


Flushing hole ϕ 22,6 mm, Female end ϕ 87 mm

Drill tube rods




Diameter		Threads	Length			Weight	Catalogue no.
mm	inch		mm	ft	inch	kg	
87	3 ½	GT60/GT60	3660	12	-	97,2	1287G60G60366
87	3 ½	GT60/GT60	4265	14	-	112,4	1287G60G60426

Drill tube rods




Diameter		Threads	Length			Weight	Catalogue no.
mm	inch		mm	ft	inch	kg	
87	3 ½	GT60/GT60	3660	12	-	100,8	1387G60G60366
87	3 ½	GT60/GT60	4265	14	-	115,9	1387G60G60426

Coupling sleeve



Diameter		Threads	Length		Weight	Catalogue no.
mm	inch		mm	inch	kg	
85	3 ⅜	GT60/T51	285	11 ¼	7,6	3985G60T5100
85	3 ⅜	GT60/GT60	320	12 ⅝	7,9	3985G60G6000

M-F adapters




Threads	Length		Weight	Catalogue no.
	mm	inch	kg	
GT60/T51	300	11 ³ / ₄	6,2	3985G60T5103


M-M adapters




Threads	Length		Weight	Catalogue no
	mm	inch	kg	
GT60/GT60	340	13 ³ / ₈	6,4	3860G60G6000



DRILLING TOOLS





GONAR Co. Ltd., 109 Obroki Str., 40-833 Katowice, Poland

Phone: +48 32 207 12 00, Fax: +48 32 207 12 50

Sales department – Phone: +48 32 207 12 16÷18, Fax: +48 32 254 03 11

E-mail: gonar@gonar.com.pl

www.gonar.com.pl